# NSN 5950-00-519-4659

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-519-4659

### **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

3.688 inches single mounting facility single center group

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

#### **Overall Height:**

6.781 inches

#### **Frequency Rating:**

60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

**Body Length:** 

4.688 inches

Body Width:

### 4.000 inches

**Body Height:** 

6.000 inches

Inclosure Type:

Fully enclosed

#### **Mounting Facility Quantity:**

4 single group

#### Mounting Method:

Threaded stud single group

#### Winding Function And Quantity:

1 primary single component and 2 secondary single component

#### Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

#### Winding Operating Current:

2.25 amperes ac single component 1st secondary

#### Winding Operating Voltage:

5.00 ac volts single component 2nd secondary26.00 ac volts single component 1st secondary

#### Thread Series Designator:

Unc single group

#### **Terminal Type And Quantity:**

6 standoff, solder lug

Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 5950-00-519-4659

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

