

View Online at <https://aerobasegroup.com/nsn/5950-00-519-5718>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

3.062 inches

Body Width:

3.062 inches

Body Height:

3.938 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

3.5 amperes dc single component 2nd secondary

Winding Operating Voltage:

4.50 ac volts single component 3rd secondary or 10.00 ac volts single component 3rd secondary or 137.50 ac volts single component 3rd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

17 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0