NSN 5950-00-519-9550

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-519-9550

| V | iew Online at https://aerobasegroup.com/nsn/5950-00-519-9550 |
|----|---|
| R | Reliability Indicator: |
| Ν | lot established |
| С | Center To Center Distance Between Mounting Facilities Parallel To Lengt |
| 1 | .560 inches single mounting facility single center group |
| С | Center To Center Distance Between Mounting Facilities Parallel To Width |
| 1 | .750 inches single mounting facility single center group |
| F | requency Rating: |
| 3 | 80.0 hertz single component and 420.0 hertz single component |
| Ir | nput-output Phase Relationship: |
| т | hree phase to three phase single component |
| B | Body Length: |
| 3 | .370 inches |
| B | Body Width: |
| 2 | .750 inches |
| B | Body Height: |
| 2 | .500 inches |
| Ir | nclosure Type: |
| F | lermetically sealed |
| N | Iounting Facility Quantity: |
| 4 | single group |
| N | Iounting Method: |
| т | hreaded hole single group |
| v | Vinding Function And Quantity: |
| 1 | primary single component and 1 secondary single component |
| Т | hready Qty Per Inch (tpi): |
| 3 | 2 single group |
| Т | hread Size: |
| 0 | .138 inches single group |
| V | Vinding Operating Current: |
| 3 | 00.0 milliamperes ac single component single secondary |
| V | Vinding Operating Voltage: |
| 2 | 00.00 ac volts single component single primary |
| т | hread Series Designator: |
| ι | Inc single group |
| Т | erminal Type And Quantity: |
| 7 | tab, solder lug |
| S | Shelf Life: |
| Ν | I/a |
| U | Init Of Measure: |
| | |
| D | Demilitarization: |
| ĸ | lo |

NSN 5950-00-519-9550

Power Transformer - Page 2 of 2

Fiig: A058b0

