## NSN 5950-00-519-9848

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-519-9848

Rε	lia	ıbil	ity	Ind	icato	r:

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

2.609 inches single mounting facility single center group and 2.641 inches single mounting facility single center group

### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.109 inches single mounting facility single center group and 2.141 inches single mounting facility single center group

## **Frequency Rating:**

60.0 hertz single component

### Input-output Phase Relationship:

Single phase to single phase single component

### **Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:** 

4.875 inches

**Body Width:** 

3.562 inches

**Body Height:** 

3.062 inches

## **Maximum Operating Temp:**

85.0 degrees celsius

## Inclosure Type:

Hermetically sealed

### **Mounting Facility Quantity:**

4 single group

## **Mounting Method:**

Threaded stud single group

## **Winding Function And Quantity:**

1 primary single component and 4 secondary single component

#### Thready Qty Per Inch (tpi):

20 single group

## **Thread Size:**

0.250 inches single group

## **Winding Operating Current:**

300.0 milliamperes ac single component 1st secondary

## **Winding Operating Voltage:**

6.40 ac volts single component 2nd secondary6.40 ac volts single component 1st secondary

## **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

10 tab, solder lug

## Shelf Life:

N/a

# NSN 5950-00-519-9848

Power Transformer - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A058b0