NSN 5950-00-519-9848

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-519-9848

Rε	lia	bili	ty	Ind	icate	or:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.609 inches single mounting facility single center group and 2.641 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.109 inches single mounting facility single center group and 2.141 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

4.875 inches

Body Width:

3.562 inches

Body Height:

3.062 inches

Maximum Operating Temp:

85.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

300.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

6.40 ac volts single component 2nd secondary6.40 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

NSN 5950-00-519-9848

Power Transformer - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A058b0