

View Online at <https://aerobasegroup.com/nsn/5950-00-521-1209>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.625 inches single mounting facility single center group2.625 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component and 60.0 hertz single component and 400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

Body Length:

4.500 inches 4.500 inches

Body Width:

3.500 inches 3.500 inches

Body Height:

4.875 inches 4.875 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

Winding Operating Current:

9.0 amperes ac single component 1st secondary

Winding Operating Voltage:

430.00 ac volts single component 2nd secondary105.00 ac volts single component single primary and 117.00 ac volts single component single primary and 125.00 ac volts single component single primary

Terminal Type And Quantity:

11 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0