

View Online at <https://aerobasegroup.com/nsn/5950-00-521-1209>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.125 inches single mounting facility single center group3.125 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.625 inches single mounting facility single center group2.625 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component and 60.0 hertz single component and 400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

**Body Length:**

4.500 inches 4.500 inches

**Body Width:**

3.500 inches 3.500 inches

**Body Height:**

4.875 inches 4.875 inches

**Inclosure Type:**

Hermetically sealedhermetically sealed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

**Winding Operating Current:**

9.0 amperes ac single component 1st secondary

**Winding Operating Voltage:**

430.00 ac volts single component 2nd secondary105.00 ac volts single component single primary and 117.00 ac volts single component single primary and 125.00 ac volts single component single primary

**Terminal Type And Quantity:**

11 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0