

View Online at <https://aerobasegroup.com/nsn/5950-00-521-2663>

Reliability Indicator:

Not establishednot established

Mounting Hole Diameter:

0.190 inches single group0.190 inches single group

Frequency Rating:

50.0 hertz single component or 50.0 hertz single component or 60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single componentinternal shield grounded to inclosure and core single component

Body Length:

2.380 inches 2.380 inches

Body Width:

1.625 inches 1.625 inches

Body Height:

1.970 inches 1.970 inches

Maximum Operating Temp:

55.0 degrees celsius55.0 degrees celsius

Distance Between Mounting Facility Centers:

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

2 single group2 single group

Mounting Method:

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Winding Operating Voltage:

7.00 ac volts single component single secondary272.00 ac volts single component single primary

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0