

View Online at <https://aerobasegroup.com/nsn/5950-00-523-8324>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches single mounting facility single center group3.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group3.000 inches single mounting facility single center group

Overall Height:

6.263 inches 6.263 inches

Frequency Rating:

50.0 hertz single component or 50.0 hertz single component or 60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internally shielded single componentinternally shielded single component

Body Length:

4.563 inches 4.563 inches

Body Width:

4.125 inches 4.125 inches

Body Height:

5.313 inches 5.313 inches

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.190 inches single group0.190 inches single group

Winding Operating Current:

500.0 milliamperes dc single component 2nd secondary

Winding Operating Voltage:

2.00 ac volts single component 1st secondary and 6.00 ac volts single component single primary and 4.00 ac volts single component 1st secondary and 95.00 ac volts single component single primary and 105.00 ac volts single component single primary and 6.00 ac volts single component 1st secondary and 115.00 ac volts single component single primary and 8.00 ac volts single component 1st secondary and 90.00 ac volts single component 1st secondary and 190.00 ac volts single component single primary and 100.00 ac volts single component 1st secondary and 210.00 ac volts single component single primary and 230.00 ac volts single component single primary and 110.00 ac volts single component 1st secondary250.00 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

20 turret

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0