

View Online at <https://aerobasegroup.com/nsn/5950-00-523-8388>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.620 inches single mounting facili type 2nd center group and 0.630 inches single mounting facili type 2nd center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.620 inches single mounting facili type 2nd center group and 0.630 inches single mounting facili type 2nd center group

**Frequency Rating:**

455.0 kilohertz single component

**Coil Form Type:**

Hollow single component

**Adjustment Device Drive Type:**

Slotted screw single component

**Winding Shielding Method:**

Internally shielded single component

**Body Length:**

Between 0.828 inches and 0.860 inches

**Body Width:**

Between 0.828 inches and 0.860 inches

**Body Height:**

Between 1.657 inches and 2.033 inches

**Distance Between Mounting Facility Centers:**

0.558 inches single mounting facili type 1st center group and 0.568 inches single mounting facili type 1st center group

**Inclosure Type:**

Open

**Mounting Facility Quantity:**

4 2nd group

**Mounting Method:**

Threaded stud 2nd group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Features Provided:**

W/capacitor and w/resistor

**Thread Size:**

0.112 inches all groupings

**Adjustment Method And Quantity:**

1 adjustable core single component

**Thread Series Designator:**

Unc all groupings

**Terminal Type And Quantity:**

5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0