

View Online at <https://aerobasegroup.com/nsn/5950-00-525-5520>

Reliability Indicator:

Not establishednot established

Mounting Hole Diameter:

0.125 inches single group0.125 inches single group

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

Body Length:

1.700 inches 1.700 inches

Body Width:

1.000 inches 1.000 inches

Body Height:

1.000 inches 1.000 inches

Maximum Operating Temp:

85.0 degrees celsius85.0 degrees celsius

Distance Between Mounting Facility Centers:

1.390 inches single mounting facility single center group1.390 inches single mounting facility single center group

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

2 single group2 single group

Mounting Method:

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

Winding Operating Current:

1.1 amperes dc single component 1st secondary

Winding Operating Voltage:

19.50 ac volts single component 2nd secondary19.50 ac volts single component 2nd secondary

Terminal Type And Quantity:

8 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0