## NSN 5950-00-528-1064

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-528-1064

### **Reliability Indicator:**

Not established

### **Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.300 inches single mounting facility single center group

### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.000 inches single mounting facility single center group

#### **Overall Height:**

2.300 inches

#### **Inductance Type:**

Fixed

#### **Inductance Rating:**

15.50 millihenries single component single winding

#### Frequency Rating:

90.0 hertz single component and 840.0 hertz single component

#### **Body Length:**

1.590 inches

#### **Body Width:**

1.390 inches

### **Maximum Operating Temp:**

95.0 degrees celsius

### **Winding Quantity:**

1 single component

### Inclosure Type:

Fully enclosed

### **Mounting Facility Quantity:**

4 single group

### **Mounting Method:**

Threaded hole single group

### Rating Method:

Electrical single component single winding

#### **Thread Size:**

0.112 inches single group

### **Winding Operating Current:**

0.925 amperes dc single component single winding

### Dc Resistance Rating In Ohms:

0.760 single component single winding

### **Special Features:**

Pin m is used for core and case grounding

### **Thread Series Designator:**

Unc single group

### **Terminal Type And Quantity:**

3 pin

# NSN 5950-00-528-1064

Reactor - Page 2 of 2



he			

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0