# NSN 5950-00-528-8177

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-528-8177

## **Reliability Indicator:**

Not establishednot established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group2.500 inches single mounting facility single center group

## Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

## Frequency Rating:

60.0 hertz single component60.0 hertz single component

## Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

## Winding Shielding Method:

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

## Body Length:

3.000 inches 3.000 inches

## Body Width:

2.500 inches 2.500 inches

#### **Body Height:**

2.450 inches 2.450 inches

### Inclosure Type:

Fully enclosedfully enclosed

### Mounting Facility Quantity:

4 single group4 single group

### **Mounting Method:**

Threaded hole single groupthreaded hole single group

### Winding Function And Quantity:

2 primary single component and 2 primary single component and 2 secondary single component2 secondary single component

### Thready Qty Per Inch (tpi):

32 single group32 single group

### Thread Size:

0.164 inches single group0.164 inches single group

### Winding Operating Voltage:

9.20 ac volts single component 2nd secondary27.20 ac volts single component 1st secondary

## Thread Series Designator:

Unc single group

## Terminal Type And Quantity:

10 wire lead

## Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5950-00-528-8177

Power Transformer - Page 2 of 2

**Fiig:** A058b0

