NSN 5950-00-530-4612

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-530-4612

Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Fungus proof and fungus resistant and moisture proof and vibration proof
Overall Length:
0.600 inches
Turn Quantity:
108-1/2 single component single winding
Overall Height:
0.600 inches
Overall Width:
0.600 inches
nductance Type:
Fixed
nductance Rating:
1.00 millihenries single component single winding
Frequency Rating:
2.4 kilohertz single component
Maximum Operating Temp:
55.0 degrees celsius
Winding Quantity:
1 single component
nclosure Type:
Fully enclosed
Mounting Method:
Terminal single group
Rating Method:
Electrical single component single winding and winding turns single component single winding
Winding Conductor Size:
0.01420 inches american wire gage single component single winding
Winding Operating Current:
0.7 amperes dc single component single winding
Dc Resistance Rating In Ohms:
0.470 single component single winding
Test Data Document:
09966-c235a109 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5950-00-530-4612

Reactor - Page 2 of 2



em			

No

Fiig:

A058b0