

View Online at <https://aerobasegroup.com/nsn/5950-00-535-4442>

Reliability Indicator:

Not establishednot established

Overall Height:

3.126 inches 3.126 inches

Frequency Rating:

380.0 hertz single component and 380.0 hertz single component and 420.0 hertz single component420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single componentinternal shield grounded to inclosure and core single component

Body Length:

2.656 inches 2.656 inches

Body Width:

2.344 inches 2.344 inches

Body Height:

2.438 inches 2.438 inches

Maximum Operating Temp:

75.0 degrees celsius75.0 degrees celsius

Distance Between Mounting Facility Centers:

1.250 inches single mounting facility single center group1.250 inches single mounting facility single center group

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

2 single group2 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

Thready Qty Per Inch (tpi):

24 single group24 single group

Thread Size:

0.190 inches single group0.190 inches single group

Winding Operating Current:

1.8 amperes ac single component 1st secondary

Winding Operating Voltage:

6.30 ac volts single component 1st secondary6.30 ac volts single component 3rd secondary26.00 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 standoff, wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0