## NSN 5950-00-535-9682

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-535-9682

### **Reliability Indicator:**

Not established

#### **Turn Quantity:**

4550 single component single winding

## Inductance Type:

Fixed

#### Inductance Rating:

2.00 henry single component single winding

#### **Frequency Rating:**

800.0 hertz single component

#### **Body Length:**

2.156 inches

#### **Body Width:**

1.906 inches

## **Body Height:**

2.250 inches

## Maximum Operating Temp:

170.0 degrees celsius

## **Distance Between Mounting Facility Centers:**

0.938 inches single mounting facility single center group

#### Winding Quantity:

1 single component

#### Inclosure Type:

Hermetically sealed

## **Mounting Facility Quantity:**

2 single group

#### **Mounting Method:**

Threaded stud single group

## **Rating Method:**

Electrical single component single winding and winding turns single component single winding

#### Thready Qty Per Inch (tpi):

32 single group

#### **Thread Size:**

0.164 inches single group

#### Winding Conductor Size:

0.00562 inches american wire gage single component single winding

#### Winding Operating Current:

60.0 milliamperes dc single component single winding

### Dc Resistance Rating In Ohms:

410.000 single component single winding

#### **Thread Series Designator:**

Unc single group

# NSN 5950-00-535-9682

Reactor - Page 2 of 2



2 wire hook

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0

