## NSN 5950-00-538-0033

Power Autotransformer Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-538-0033

Pattabilita in the sea
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.375 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.375 inches single mounting facility single center group
Frequency Rating:
380.0 hertz single component and 2.0 kilohertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
2.880 inches
Body Width:
2.500 inches
Body Height:
2.500 inches
Inclosure Type:
Partially enclosed, half shell
Mounting Facility Quantity:
8 single group
Mounting Method:
Unthreaded hole single group
Winding Function And Quantity:
1 primary, fixed autotransformer type single component
Winding Operating Current:
9.5 amperes ac single component single primary output and 10.0 amperes ac single component single primary output and 10.5 amperes ac
single component single primary output and 11.0 amperes ac single component single primary output
Winding Operating Voltage:
95.00 ac volts single component single primary output and 100.00 ac volts single component single primary output and 105.00 ac volts
single component single primary output and 110.00 ac volts single component single primary output
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No .
Fiig:
A058b0