

View Online at <https://aerobasegroup.com/nsn/5950-00-538-0033>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.375 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 2.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.880 inches

Body Width:

2.500 inches

Body Height:

2.500 inches

Inclosure Type:

Partially enclosed, half shell

Mounting Facility Quantity:

8 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary, fixed autotransformer type single component

Winding Operating Current:

9.5 amperes ac single component single primary output and 10.0 amperes ac single component single primary output and 10.5 amperes ac single component single primary output and 11.0 amperes ac single component single primary output

Winding Operating Voltage:

95.00 ac volts single component single primary output and 100.00 ac volts single component single primary output and 105.00 ac volts single component single primary output and 110.00 ac volts single component single primary output

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0