

View Online at <https://aerobasegroup.com/nsn/5950-00-538-1835>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.438 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.406 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

2.062 inches

Body Width:

2.000 inches

Body Height:

2.250 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

10.0 amperes ac single component 2nd secondary

Winding Operating Voltage:

6.30 ac volts single component all secondary 115.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0