## NSN 5950-00-538-2338

Power Transformer - Page 1 of 1

Fiig: A058b0



View Online at https://aerobasegroup.com/nsn/5950-00-538-2338

| View Online at https://aerobasegroup.com/nsn/5950-00-538-2338  |
|--|
| Reliability Indicator:   |
| Not establishednot established   |
| Mounting Hole Diameter:  |
| 0.188 inches single group0.188 inches single group   |
| Frequency Rating:  |
| 50.0 hertz single component or 50.0 hertz single component or 60.0 hertz single component60.0 hertz single component   |
| Input-output Phase Relationship:   |
| Single phase to single phase single componentsingle phase to single phase single component                             |
| Body Length:   |
| 3.312 inches 3.312 inches  |
| Body Width:  |
| 2.000 inches 2.000 inches  |
| Body Height:   |
| 1.938 inches 1.938 inches  |
| Distance Between Mounting Facility Centers:  |
| 2.812 inches single mounting facility single center group2.812 inches single mounting facility single center group     |
| Inclosure Type:  |
| Openopen   |
| Mounting Facility Quantity:  |
| 2 single group2 single group   |
| Mounting Method:   |
| Unthreaded hole single groupunthreaded hole single group   |
| Winding Function And Quantity:   |
| 1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component |
| Winding Operating Current:   |
| 3.0 amperes ac single component single secondary   |
| Winding Operating Voltage:   |
| 6.30 ac volts single component single secondary115.00 ac volts single component single primary                         |
| Terminal Type And Quantity:  |
| 5 wire lead  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| - <del>-</del>   |
| Demilitarization:  |
| No   |