

View Online at <https://aerobasegroup.com/nsn/5950-00-538-3661>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.937 inches single mounting facility single center group2.937 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.437 inches single mounting facility single center group2.437 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Body Length:**

Between 3.526 inches and 3.526 inches and 3.536 inches 3.536 inches

**Body Width:**

Between 2.995 inches and 2.995 inches and 3.005 inches 3.005 inches

**Body Height:**

Between 4.870 inches and 4.870 inches and 4.880 inches 4.880 inches

**Inclosure Type:**

Hermetically sealedhermetically sealed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

**Thread Size:**

0.164 inches single group

**Winding Operating Current:**

960.0 milliamperes ac single component 1st secondary

**Winding Power Rating:**

22.0 watts single component single primary

**Winding Operating Voltage:**

86.30 ac volts single component 1st secondary628.00 ac volts single component single primary114.00 ac volts single component 2nd secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

8 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0