NSN 5950-00-538-4042

Electrical Coil - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-538-4042

Reliability Indicator:
Not established
Turn Quantity:
430 single component single winding
Mounting Slot Width:
0.656 inches single group
Body Length:
2.210 inches
Body Width:
1.840 inches
Body Height:
1.810 inches
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
1 single group
Mounting Method:
Slot single group
Rating Method:
Rating Method: Electrical single component single winding and winding turns single component single winding
-
Electrical single component single winding and winding turns single component single winding
Electrical single component single winding and winding turns single component single winding Winding Conductor Size:
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02010 inches american wire gage single component single winding
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02010 inches american wire gage single component single winding Winding Operating Current:
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02010 inches american wire gage single component single winding Winding Operating Current: 7.85 amperes ac single component single winding
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02010 inches american wire gage single component single winding Winding Operating Current: 7.85 amperes ac single component single winding Dc Resistance Rating In Ohms:
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02010 inches american wire gage single component single winding Winding Operating Current: 7.85 amperes ac single component single winding Dc Resistance Rating In Ohms: 14.000 single component single winding
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02010 inches american wire gage single component single winding Winding Operating Current: 7.85 amperes ac single component single winding Dc Resistance Rating In Ohms: 14.000 single component single winding Winding Operating Voltage:
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02010 inches american wire gage single component single winding Winding Operating Current: 7.85 amperes ac single component single winding Dc Resistance Rating In Ohms: 14.000 single component single winding Winding Operating Voltage: 10.00 ac pounds per hour wet single component single winding
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02010 inches american wire gage single component single winding Winding Operating Current: 7.85 amperes ac single component single winding Dc Resistance Rating In Ohms: 14.000 single component single winding Winding Operating Voltage: 10.00 ac pounds per hour wet single component single winding Terminal Type And Quantity:
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02010 inches american wire gage single component single winding Winding Operating Current: 7.85 amperes ac single component single winding Dc Resistance Rating In Ohms: 14.000 single component single winding Winding Operating Voltage: 10.00 ac pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02010 inches american wire gage single component single winding Winding Operating Current: 7.85 amperes ac single component single winding Dc Resistance Rating In Ohms: 14.000 single component single winding Winding Operating Voltage: 10.00 ac pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life:
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02010 inches american wire gage single component single winding Winding Operating Current: 7.85 amperes ac single component single winding Dc Resistance Rating In Ohms: 14.000 single component single winding Winding Operating Voltage: 10.00 ac pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02010 inches american wire gage single component single winding Winding Operating Current: 7.85 amperes ac single component single winding Dc Resistance Rating In Ohms: 14.000 single component single winding Winding Operating Voltage: 10.00 ac pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02010 inches american wire gage single component single winding Winding Operating Current: 7.85 amperes ac single component single winding Dc Resistance Rating In Ohms: 14.000 single component single winding Winding Operating Voltage: 10.00 ac pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02010 inches american wire gage single component single winding Winding Operating Current: 7.85 amperes ac single component single winding Dc Resistance Rating In Ohms: 14.000 single component single winding Winding Operating Voltage: 10.00 ac pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: