

View Online at <https://aerobasegroup.com/nsn/5950-00-538-4962>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.312 inches single mounting facility single center group1.312 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.000 inches single mounting facility single center group1.000 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

**Body Length:**

1.734 inches 1.734 inches

**Body Width:**

1.563 inches 1.563 inches

**Body Height:**

1.844 inches 1.844 inches

**Inclosure Type:**

Hermetically sealedhermetically sealed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 4 secondary single component4 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group32 single group

**Thread Size:**

0.138 inches single group0.138 inches single group

**Winding Operating Current:**

600.0 milliamperes ac single component 2nd secondary

**Winding Operating Voltage:**

6.30 ac volts single component 1st secondary12.70 ac volts single component 2nd secondary8.00 ac volts single component 4th secondary and 28.00 ac volts single component 4th secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

13 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0