NSN 5950-00-538-5008

Power Autotransformer Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-538-5008

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.375 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.125 inches single mounting facility single center group
Mounting Slot Width:
0.199 inches single group
Frequency Rating:
60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
3.000 inches
Body Width:
3.750 inches
Body Height:
3.188 inches
Inclosure Type:
Open
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and slot single group
Winding Function And Quantity:
1 primary, fixed autotransformer type single component
Winding Power Rating:
60.0 volts-amperes single component single primary input
Winding Operating Voltage:
20.00 ac volts single component single primary output and 200.00 ac volts single component single primary output
20.00 ac volts single component single primary output and 200.00 ac volts single component single primary output
20.00 ac volts single component single primary output and 200.00 ac volts single component single primary output Terminal Type And Quantity:
20.00 ac volts single component single primary output and 200.00 ac volts single component single primary output Terminal Type And Quantity: 4 tab, solder lug
20.00 ac volts single component single primary output and 200.00 ac volts single component single primary output Terminal Type And Quantity: 4 tab, solder lug Shelf Life:
20.00 ac volts single component single primary output and 200.00 ac volts single component single primary output Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a
20.00 ac volts single component single primary output and 200.00 ac volts single component single primary output Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a
20.00 ac volts single component single primary output and 200.00 ac volts single component single primary output Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure:
20.00 ac volts single component single primary output and 200.00 ac volts single component single primary output Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: