NSN 5950-00-538-5009

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-538-5009

Note established Center To Center Distance Between Mounting Facilities Parallel To Length: 4.500 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.875 inches single mounting facility single center group Mounting Slot Width: 0.188 inches single group Frequency Rating: 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 5.750 inches Body Width: 3.500 inches Body Height: 3.500 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Center To Center Distance Between Mounting Facilities Parallel To Length: 4.500 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.875 inches single mounting facility single center group Mounting Slot Width: 0.188 inches single group Frequency Rating: 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 5.750 inches Body Width: 3.500 inches Body Height: 3.500 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Reliability Indicator:
4.500 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.875 inches single mounting facility single center group Mounting Slot Width: 0.188 inches single group Frequency Rating: 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 5.750 inches Body Width: 3.500 inches Body Height: 3.500 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Center To Center Distance Between Mounting Facilities Parallel To Width: 2.875 inches single mounting facility single center group Mounting Slot Width: 0.188 inches single group Frequency Rating: 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 5.750 inches Body Width: 3.500 inches Body Height: 3.500 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
2.875 inches single mounting facility single center group Mounting Slot Width: 0.188 inches single group Frequency Rating: 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 5.750 inches Body Width: 3.500 inches Body Height: 3.500 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Mounting Slot Width: 0.188 inches single group Frequency Rating: 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 5.750 inches Body Width: 3.500 inches Body Height: 3.500 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Co.188 inches single group Frequency Rating: 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 5.750 inches Body Width: 3.500 inches Body Height: 3.500 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	2.875 inches single mounting facility single center group
Frequency Rating: 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 5.750 inches Body Width: 3.500 inches Body Height: 3.500 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Mounting Slot Width:
60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 5.750 inches Body Width: 3.500 inches Body Height: 3.500 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.188 inches single group
Input-output Phase Relationship: Single phase to single phase single component Body Length: 5.750 inches Body Width: 3.500 inches Body Height: 3.500 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Frequency Rating:
Single phase to single phase single component Body Length: 5.750 inches Body Width: 3.500 inches Body Height: 3.500 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	60.0 hertz single component
Body Length: 5.750 inches Body Width: 3.500 inches Body Height: 3.500 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Input-output Phase Relationship:
5.750 inches Body Width: 3.500 inches Body Height: 3.500 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Single phase to single phase single component
Body Width: 3.500 inches Body Height: 3.500 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
3.500 inches Body Height: 3.500 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	5.750 inches
Body Height: 3.500 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Width:
3.500 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	3.500 inches
Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Height:
Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	3.500 inches
Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Inclosure Type:
4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Partially enclosed, double shell
Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Mounting Facility Quantity:
Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	4 single group
Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Mounting Method:
1 primary single component and 1 secondary single component Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Flange single group and slot single group
Winding Operating Voltage: 440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Winding Function And Quantity:
440.00 ac pounds per hour wet single component single primary Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1 primary single component and 1 secondary single component
Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Winding Operating Voltage:
4 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	440.00 ac pounds per hour wet single component single primary
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No Fiig:	4 wire lead
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A058b0	Fiig:
. 1.00020	A058b0