# NSN 5950-00-538-5662

Power Autotransformer Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-538-5662

# **Reliability Indicator:**

Not established

#### **Hazardous Locations/environmental Protection:**

Vibration resistant and humidity resistant

# Center To Center Distance Between Mounting Facilities Parallel To Length:

2.750 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.750 inches single mounting facility single center group

#### **Overall Height:**

3.750 inches

#### **Mounting Hole Diameter:**

0.265 inches single group

#### Frequency Rating:

350.0 hertz single component and 1.2 kilohertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Body Length:**

3.250 inches

# **Body Width:**

3.250 inches

# **Inclosure Type:**

Open

#### **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Flange single group and unthreaded hole single group

# **Winding Function And Quantity:**

1 primary, variable autotransformer type single component

#### **Winding Operating Current:**

3.1 amperes ac single component single primary output

# **Winding Power Rating:**

370.0 volts-amperes single component single primary input

# **Winding Operating Voltage:**

120.00 ac volts single component single primary input

# **Terminal Type And Quantity:**

5 tab, solder lug

#### Shelf Life:

N/a

# **Unit Of Measure:**

--

#### **Demilitarization:**

No

# NSN 5950-00-538-5662

Power Autotransformer Transformer - Page 2 of 2



Fiig:

A058b0