

View Online at <https://aerobasegroup.com/nsn/5950-00-538-6047>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.938 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.750 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Maximum Transformer Power Rating:**

60.0 volt-ampere single component

**Body Length:**

6.688 inches

**Body Width:**

4.781 inches

**Body Height:**

5.562 inches

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Flange single group and unthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Winding Operating Current:**

1.8 amperes ac single component single secondary

**Winding Operating Voltage:**

70.00 ac pounds per hour wet single component single secondary

**Special Features:**

A fixed 30 uf capacitor must be connected across terminals 3 and 4 to obtain constant output voltage

**Terminal Type And Quantity:**

4 ferrule clip

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0