

View Online at <https://aerobasegroup.com/nsn/5950-00-538-6236>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.875 inches single mounting facility single center group2.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.062 inches single mounting facility single center group2.062 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

3.594 inches 3.594 inches

Body Width:

3.125 inches 3.125 inches

Body Height:

4.156 inches 4.156 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

1 single group1 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thready Qty Per Inch (tpi):

24 single group24 single group

Thread Size:

0.190 inches single group0.190 inches single group

Winding Operating Current:

200.0 milliamperes ac single component single secondary

Winding Operating Voltage:

45.00 ac volts single component single primary and 78.00 ac volts single component single primary and 90.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0