

View Online at <https://aerobasegroup.com/nsn/5950-00-538-7137>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.734 inches single mounting facility all center groupings and 1.766 inches single mounting facility all center groupings

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.932 inches single mounting facili type 2nd center group and 0.942 inches single mounting facili type 2nd center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internally shielded single component

Body Length:

Between 2.250 inches and 2.313 inches

Body Width:

Between 1.734 inches and 1.766 inches

Body Height:

Between 1.813 inches and 1.875 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 all groupings

Mounting Method:

Threaded hole all groupings

Winding Function And Quantity:

1 primary, fixed autotransformer type single component

Thread Size:

0.112 inches all groupings

Winding Operating Voltage:

44.00 ac volts single component single primary output and 48.00 ac volts single component single primary output and 52.00 ac volts single component single primary output and 56.00 ac volts single component single primary output and 60.00 ac volts single component single primary output and 64.00 ac volts single component single primary output and 68.00 ac volts single component single primary output and 72.00 ac volts single component single primary output and 76.00 ac volts single component single primary output and 80.00 ac volts single component single primary output

Thread Series Designator:

Unc all groupings

Terminal Type And Quantity:

13 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Fig:

A058b0