

View Online at <https://aerobasegroup.com/nsn/5950-00-539-6778>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group1.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.375 inches single mounting facility single center group1.375 inches single mounting facility single center group

Overall Height:

2.780 inches 2.780 inches

Overall Width:

1.870 inches 1.870 inches

Frequency Rating:

60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single componentinternal shield grounded to inclosure and core single component

Body Length:

1.870 inches 1.870 inches

Maximum Operating Temp:

75.0 degrees celsius75.0 degrees celsius

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

8 single group8 single group

Mounting Method:

Threaded hole single groupthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.138 inches single group0.138 inches single group

Winding Operating Current:

125.0 milliamperes ac single component single secondary

Winding Operating Voltage:

40.00 ac volts single component single secondary115.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0