

View Online at <https://aerobasegroup.com/nsn/5950-00-539-6936>

**Reliability Indicator:**

Not establishednot establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.688 inches single mounting facility single center group1.688 inches single mounting facility single center group1.688 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.219 inches single mounting facility single center group1.219 inches single mounting facility single center group1.219 inches single mounting facility single center group

**Mounting Hole Diameter:**

0.156 inches single group0.156 inches single group0.156 inches single group

**Frequency Rating:**

330.0 hertz single component and 330.0 hertz single component and 330.0 hertz single component and 1.76 kilohertz single component1.76 kilohertz single component1.76 kilohertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single componentinternal shield brought out to terminal single componentinternal shield brought out to terminal single component

**Body Length:**

2.312 inches 2.312 inches 2.312 inches

**Body Width:**

2.125 inches 2.125 inches 2.125 inches

**Body Height:**

2.250 inches 2.250 inches 2.250 inches

**Maximum Operating Temp:**

71.0 degrees celsius71.0 degrees celsius71.0 degrees celsius

**Inclosure Type:**

Fully enclosedfully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group4 single group

**Mounting Method:**

Flange single group and flange single group and flange single group and unthreaded hole single groupunthreaded hole single groupunthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component1 secondary single component

**Winding Operating Current:**

12.0 milliamperes ac single component single secondary

**Winding Operating Voltage:**

115.00 ac volts single component single primary640.00 ac volts single component single secondary and 660.00 ac volts single component single secondary and 680.00 ac volts single component single secondary

**Terminal Type And Quantity:**

7 tab, solder lug

**Shelf Life:**

**Fig:**

A058b0