

View Online at <https://aerobasegroup.com/nsn/5950-00-539-6936>

Reliability Indicator:

Not establishednot establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.688 inches single mounting facility single center group1.688 inches single mounting facility single center group1.688 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.219 inches single mounting facility single center group1.219 inches single mounting facility single center group1.219 inches single mounting facility single center group

Mounting Hole Diameter:

0.156 inches single group0.156 inches single group0.156 inches single group

Frequency Rating:

330.0 hertz single component and 330.0 hertz single component and 330.0 hertz single component and 1.76 kilohertz single component1.76 kilohertz single component1.76 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single componentinternal shield brought out to terminal single componentinternal shield brought out to terminal single component

Body Length:

2.312 inches 2.312 inches 2.312 inches

Body Width:

2.125 inches 2.125 inches 2.125 inches

Body Height:

2.250 inches 2.250 inches 2.250 inches

Maximum Operating Temp:

71.0 degrees celsius71.0 degrees celsius71.0 degrees celsius

Inclosure Type:

Fully enclosedfully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group4 single group

Mounting Method:

Flange single group and flange single group and flange single group and unthreaded hole single groupunthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component1 secondary single component

Winding Operating Current:

12.0 milliamperes ac single component single secondary

Winding Operating Voltage:

115.00 ac volts single component single primary640.00 ac volts single component single secondary and 660.00 ac volts single component single secondary and 680.00 ac volts single component single secondary

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

Fiig:

A058b0