# NSN 5950-00-539-7098

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-539-7098

## **Reliability Indicator:**

Not establishednot established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

9.312 inches single mounting facility single center group9.312 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.312 inches single mounting facility single center group2.312 inches single mounting facility single center group

## **Mounting Hole Diameter:**

0.438 inches single group 0.438 inches single group

## Frequency Rating:

60.0 hertz single component60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

## **Maximum Transformer Power Rating:**

30.0 volt-ampere single component 30.0 volt-ampere single component

#### **Body Length:**

10.312 inches 10.312 inches

#### **Body Width:**

4.188 inches 4.188 inches

#### **Body Height:**

4.500 inches 4.500 inches

# Inclosure Type:

Fully enclosedfully enclosed

#### **Mounting Facility Quantity:**

4 single group4 single group

#### **Mounting Method:**

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

# **Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

#### **Winding Operating Current:**

75.0 milliamperes ac single component single secondary

# Winding Operating Voltage:

105.00 ac volts single component single primary and 125.00 ac volts single component single primary

## **Terminal Type And Quantity:**

4 terminal block w/screws

#### Shelf Life:

N/a

#### **Unit Of Measure:**

--

# Demilitarization:

No

#### Fiig:

A058b0