

View Online at <https://aerobasegroup.com/nsn/5950-00-539-7172>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches single mounting facility single center group2.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group2.125 inches single mounting facility single center group

Overall Height:

Between 4.000 inches and 4.000 inches and 4.313 inches 4.313 inches

Frequency Rating:

50.0 hertz single component or 50.0 hertz single component or 60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

Body Length:

Between 3.438 inches and 3.438 inches and 3.563 inches 3.563 inches

Body Width:

Between 2.938 inches and 2.938 inches and 3.063 inches 3.063 inches

Body Height:

Between 3.688 inches and 3.688 inches and 3.875 inches 3.875 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

Thread Size:

0.164 inches single group0.164 inches single group

Winding Operating Current:

2.0 amperes ac single component all secondary

Winding Operating Voltage:

12.60 ac volts single component all secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0