

View Online at <https://aerobasegroup.com/nsn/5950-00-539-7224>

Reliability Indicator:

Not establishednot established

Frequency Rating:

60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

1.312 inches 1.312 inches

Body Width:

1.312 inches 1.312 inches

Body Height:

1.750 inches 1.750 inches

Distance Between Mounting Facility Centers:

0.875 inches single mounting facility single center group0.875 inches single mounting facility single center group

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

2 single group2 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.138 inches single group0.138 inches single group

Winding Operating Current:

10.0 milliamperes ac single component single secondary

Winding Operating Voltage:

80.00 ac volts single component single secondary165.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0