

View Online at <https://aerobasegroup.com/nsn/5950-00-539-7494>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches single mounting facility single center group2.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.625 inches single mounting facility single center group2.625 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 50.0 hertz single component and 420.0 hertz single component420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single componentinternal shield grounded to inclosure and core single component

Body Length:

3.562 inches 3.562 inches

Body Width:

3.062 inches 3.062 inches

Body Height:

4.875 inches 4.875 inches

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.164 inches single group0.164 inches single group

Winding Operating Current:

2.0 amperes dc single component 2nd secondary

Winding Operating Voltage:

790.00 ac volts single component 1st secondary115.00 ac volts single component single primary and 120.00 ac volts single component single primary and 125.00 ac volts single component single primary and 132.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0