

View Online at <https://aerobasegroup.com/nsn/5950-00-539-7892>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.125 inches single mounting facility single center group3.125 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.625 inches single mounting facility single center group2.625 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component or 50.0 hertz single component or 60.0 hertz single component60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Body Length:**

4.125 inches 4.125 inches

**Body Width:**

3.500 inches 3.500 inches

**Body Height:**

4.500 inches 4.500 inches

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

2 primary single component and 2 primary single component and 2 secondary single component2 secondary single component

**Thready Qty Per Inch (tpi):**

40 single group40 single group

**Thread Size:**

0.112 inches single group0.112 inches single group

**Winding Operating Current:**

3.0 amperes ac single component 1st secondary

**Winding Operating Voltage:**

5.00 ac volts single component 1st secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

14 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0