

View Online at <https://aerobasegroup.com/nsn/5950-00-539-7892>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.625 inches single mounting facility single center group2.625 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 50.0 hertz single component or 60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

4.125 inches 4.125 inches

Body Width:

3.500 inches 3.500 inches

Body Height:

4.500 inches 4.500 inches

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

2 primary single component and 2 primary single component and 2 secondary single component2 secondary single component

Thready Qty Per Inch (tpi):

40 single group40 single group

Thread Size:

0.112 inches single group0.112 inches single group

Winding Operating Current:

3.0 amperes ac single component 1st secondary

Winding Operating Voltage:

5.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0