NSN 5950-00-542-7546

Audio Frequency Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-542-7546

Reliability Indicator: Not estabilished Center To Center Distance Between Mounting Facilities Parallel To Length: 1.375 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 0.437 inches single mounting facility single center group Mounting Hole Diameter: 0.120 inches single group Impedance Rating In Ohms: 610.0 single component single secondary Frequency Rating: 100.0 hertz single component Body Length: 1.438 inches Body Width: 1.438 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 1 spinary single component and 1 secondary single component Yinding Function And Quantity: 1 primary single component and 1 secondary single component Yinding Guerter 2 so milliamperes dc single component single secondary Yinding Guerter 5 tab, solder lug Shelf Life: Na Dirt of Measure: Treminal Type And Quantity: Yi	
Center To Center Distance Between Mounting Facilities Parallel To Length: 1.375 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 0.437 inches single mounting facility single center group Mounting Hole Diameter: 0.120 inches single group Impedance Rating In Ohms: 610.0 single component single secondary Frequency Rating: 100.0 hertz single component Body Length: 1.594 inches Body Width: 1.438 inches Body Height: 1.188 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Freminal Type And Quantity: 5 tab, solder lug Sheff Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Reliability Indicator:
1.375 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 0.437 inches single mounting facility single center group Mounting Hole Diameter: 0.120 inches single group Impedance Rating In Ohms: 610.0 single component single secondary Frequency Rating: 100.0 hertz single component Body Length: 1.594 inches Body Width: 1.438 inches Body Height: 1.188 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Not established
Center To Center Distance Between Mounting Facilities Parallel To Width: 0.437 inches single mounting facility single center group Mounting Hole Diameter: 0.120 inches single group Impedance Rating In Ohms: 610.0 single component single secondary Frequency Rating: 100.0 hertz single component Body Length: 1.594 inches Body Width: 1.438 inches Body Height: 1.188 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Center To Center Distance Between Mounting Facilities Parallel To Length:
0.437 inches single mounting facility single center group Mounting Hole Diameter: 0.120 inches single group Impedance Rating In Ohms: 610.0 single component single secondary Frequency Rating: 100.0 hertz single component Body Length: 1.594 inches Body Width: 1.438 inches Body Height: 1.438 inches Body Height: 1.188 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Sheff Life: N/a Unit of Measure: Demilitarization: No Fig:	1.375 inches single mounting facility single center group
Mounting Hole Diameter: 0.120 inches single group Impedance Rating In Ohms: 610.0 single component single secondary Frequency Rating: 100.0 hertz single component Body Length: 1.594 inches Body Width: 1.438 inches Body Height: 1.188 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit of Measure: Demilitarization: No Fig:	Center To Center Distance Between Mounting Facilities Parallel To Width:
0.120 inches single group Impedance Rating In Ohms: 610.0 single component single secondary Frequency Rating: 100.0 hertz single component Body Length: 1.594 inches Body Width: 1.438 inches Body Height: 1.438 inches Body Height: 1.188 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Sheff Life: Na Unit Of Measure: Demilitarization: No Fig:	0.437 inches single mounting facility single center group
Impedance Rating In Ohms: 610.0 single component single secondary Frequency Rating: 100.0 hertz single component Body Length: 1.594 inches Body Width: 1.594 inches Body Width: 1.438 inches Body Height: 1.188 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Sheff Life: N/a Unit Of Measure: Demilitarization: No Flig:	Mounting Hole Diameter:
610.0 single component single secondary Frequency Rating: 100.0 hertz single component Body Length: 1.594 inches Body Width: 1.438 inches Body Height: 1.188 inches Body Height: 1.188 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Shelf Life: N/a Unit Of Measure: No Flig:	0.120 inches single group
Frequency Rating: 100.0 hertz single component Body Length: 1.594 inches Body Width: 1.438 inches Body Height: 1.188 inches Body Height: 1.188 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Impedance Rating In Ohms:
100.0 hertz single component Body Length: 1.594 inches Body Width: 1.438 inches Body Height: 1.188 inches Body Height: 1.188 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	610.0 single component single secondary
Body Length: 1.594 inches Body Width: 1.438 inches Body Height: 1.188 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Minding Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Frequency Rating:
 1.594 inches Body Width: 1.438 inches Body Height: 1.188 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig: 	100.0 hertz single component
Body Width: 1.438 inches Body Height: 1.188 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
1.438 inches Body Height: 1.188 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1.594 inches
Body Height: 1.188 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Width:
1.188 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1.438 inches
Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	Body Height:
Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1.188 inches
Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	Inclosure Type:
4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Open
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Mounting Facility Quantity:
Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	4 single group
Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Mounting Method:
1 primary single component and 1 secondary single component Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Flange single group and unthreaded hole single group
Winding Operating Current: 25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Winding Function And Quantity:
25.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1 primary single component and 1 secondary single component
Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Winding Operating Current:
5 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	25.0 milliamperes dc single component single secondary
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No Fiig:	5 tab, solder lug
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	-
Fiig:	Demilitarization:
-	No
A058b0	Fiig:
	A058b0