

View Online at <https://aerobasegroup.com/nsn/5950-00-542-7573>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.437 inches 2nd mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

5.000 inches

Body Width:

4.625 inches

Body Height:

6.250 inches

Distance Between Mounting Facility Centers:

3.500 inches 1st mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 1st group 3 2nd group 2 1st group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

2 primary single component and 12 secondary single component

Thread Size:

0.250 inches 1st group

Winding Operating Current:

740.0 milliamperes ac single component 4th secondary

Winding Operating Voltage:

6.30 ac volts single component 2nd secondary 210.00 ac volts single component 1st secondary

Special Features:

2 primaries, 12 secondaries

Thread Series Designator:

Unc all groupings

Terminal Type And Quantity:

29 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0