

View Online at <https://aerobasegroup.com/nsn/5950-00-542-7573>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.437 inches 2nd mounting facility single center group

**Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

5.000 inches

**Body Width:**

4.625 inches

**Body Height:**

6.250 inches

**Distance Between Mounting Facility Centers:**

3.500 inches 1st mounting facility single center group

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

2 1st group 3 2nd group 2 1st group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

2 primary single component and 12 secondary single component

**Thread Size:**

0.250 inches 1st group

**Winding Operating Current:**

740.0 milliamperes ac single component 4th secondary

**Winding Operating Voltage:**

6.30 ac volts single component 2nd secondary 210.00 ac volts single component 1st secondary

**Special Features:**

2 primaries, 12 secondaries

**Thread Series Designator:**

Unc all groupings

**Terminal Type And Quantity:**

29 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0