

View Online at <https://aerobasegroup.com/nsn/5950-00-543-0521>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.438 inches single mounting facility single center group2.438 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.000 inches single mounting facility single center group3.000 inches single mounting facility single center group

**Frequency Rating:**

48.0 hertz single component and 48.0 hertz single component and 62.0 hertz single component62.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Body Length:**

6.125 inches 6.125 inches

**Body Width:**

3.938 inches 3.938 inches

**Body Height:**

3.375 inches 3.375 inches

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 6 secondary single component6 secondary single component

**Thread Size:**

0.190 inches single group0.190 inches single group

**Winding Operating Current:**

650.0 milliamperes dc single component 2nd secondary

**Winding Operating Voltage:**

890.00 ac volts single component 1st secondary6.30 ac volts single component 4th secondary650.00 ac volts single component 2nd secondary

**Special Features:**

Six secondaries

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

2 standoff, solder lug and 14 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0