

View Online at <https://aerobasegroup.com/nsn/5950-00-543-1015>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.312 inches single mounting facility single center group3.312 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.688 inches single mounting facility single center group2.688 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 380.0 hertz single component and 420.0 hertz single component420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

Body Length:

4.310 inches 4.310 inches

Body Width:

3.690 inches 3.690 inches

Body Height:

5.560 inches 5.560 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.138 inches single group0.138 inches single group

Winding Operating Voltage:

6.60 ac volts single component 1st secondary115.00 ac volts single component single primary and 120.00 ac volts single component single primary and 126.00 ac volts single component single primary and 132.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0