## NSN 5950-00-543-9018

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-543-9018

| view Online at https://aerobasegroup.com/nsr//5950-00-543-9018            |
|---|
| Reliability Indicator:  |
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.230 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 2.180 inches single mounting facility single center group                 |
| Frequency Rating:   |
| 50.0 hertz and 60.0 hertz single component                                |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Winding Shielding Method:   |
| Internal shield grounded to inclosure single component                    |
| Body Length:  |
| 3.310 inches  |
| Body Width:   |
| 2.880 inches  |
| Body Height:  |
| 3.560 inches  |
| Inclosure Type:   |
| Partially enclosed, double shell  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Flange and unthreaded hole single group                                   |
| Winding Function And Quantity:  |
| 1 primary and 3 secondary single component                                |
| Winding Operating Current:  |
| 90.0 milliamperes ac single component 2nd secondary                       |
| Winding Operating Voltage:  |
| 6.30 ac volts single component 3rd secondary                              |
| Terminal Type And Quantity:   |
| 10 wire lead  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |

A058b0