NSN 5950-00-543-9251

Audio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-543-9251

Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 3.250 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 3.000 inches single mounting facility single center group Impedance Rating In Ohms: 200.0 single component single primary Frequency Rating: 60.0 hertz single component Maximum Transformer Power Rating: 120.0 watts single component Winding Shielding Method: Core grounded single component Bridy Utith 4.500 inches Body Length: 4.500 inches Body Utith: 4.500 inches Body Width: 4.500 inches Body Height: 5.500 inches Inclosure Type: Hermetically sealed Mounting Method: Threaded stud single group Mounting Facility Quantity: 1 inpray single component and 2 secondary single component Thready type Inch (tpi): 3 single group Thready Single group Minding Shieb Single group Th	Poliobility Indicator
Center To Center Distance Between Mounting Facilities Parallel To Length: 3.250 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 3.000 inches single mounting facility single center group Impedance Rating In Ohms: 200.0 single component single primary Frequency Rating: 60.0 hertz single component Maximum Transformer Power Rating: 120.0 watts single component Maximum Transformer Power Rating: 120.0 watts single component Primary To Secondary Turn Ratic: 1 to 5 10 9 single component Winding Shielding Method: Core grounded single component Body Length: 4.500 inches Body Length: 4.500 inches Body Height: 5.500 inches Body Height: 5.500 inches Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component ascondary single component Thready Cy Per Inch (tpi): 22 single group Munting Quereting Quantity: 4 single group Munting Genuponent and Secondary single component Thready Cy Per Inch (tpi): 22 single group Munting Quereting Quantity: 1 primary single component and Secondary single component Thread Stud single group Minding Quereting Quantity: 23 single group Munting Appendic Quantity: 24 single group Munting Quereting Quantity: 25 single group Minding Quereting Quantity: 25 single group Minding Quereting Quantity: 26 single group Minding Quereting Quantity: 27 thread Stud Single component single primary Thread Stud Single group Minding Quereting Quantity: 7 thread Stud Single Component single primary Thread Stud Single group Minding Quereting Quantity: 7 the soiled ruge 7 the soiled ruge	Reliability Indicator:
 3.250 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 3.000 inches single mounting facility single center group Impedance Rating In Ohms: 200.0 single component single primary Frequency Rating: 60.0 hertz single component Maximum Transformer Power Rating: 120.0 watts single component Primary To Secondary Turn Ratio: 1 to 5 10 9 single component Winding Shielding Method: Core grounded single component Body Length: 4.500 inches Body Width: 4.500 inches Body Height: 5.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mining Method: Thread Stud single group Winding Function And Quantity: 1 primary single component and 2 secondary single component 2 single group Thread Stud: 1 primary single component and 2 secondary single component 2 single group Chread Stud single group Winding Method: Core primary single component and 2 secondary single component 2 single group Thread Stud: 2 single group Chread Stud single group Winding Operating Current: 2 single group Chread Stud single group Winding Operating Current: 2 sold rulu; 2 single group Chread Stud single group Winding Operating Current: 2 sold rulu; 2 single group Chread Stud single g	
Center To Center Distance Between Mounting Facilities Parallel To Width: 3.000 inches single mounting facility single center group Impedance Rating In Ohms: 20.0 single component single primary Frequency Rating: 60.0 hertz single component Maximum Transformer Power Rating: 120.0 watts single component Primary To Secondary Turn Ratio: 1 to 5 10 9 single component Winding Shielding Method: Core grounded single component Body Length: 4.500 inches Body Width: 4.000 inches Body Width: 4.000 inches Body Width: 4.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threade stud single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Thready Quy Per Inch (tpi): 32 single group Minding Operating Current: 2.0.0 milliamperes dc single component single primary Thread Steis group Minding Opera	
3.000 inches single mounting facility single center group Impedance Rating In Ohms: 200.0 single component single primary Frequency Rating: 60.0 hertz single component Maximum Transformer Power Rating: 120.0 watts single component Primary To Secondary Turn Ratio: 1 to 5 to 9 single component Winding Shielding Method: Core grounded single component Body Length: 4.500 inches Body Width: 4.000 inches Body Height: 5.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 4 single group Minding Method: Threaded stud single group Minding Function And Quantity: 1 primary single component and 2 secondary single component Thready Gty Per Inch (tpi): 32 single group Minding Operating Current: 20.0 milliamperes de single component single primary Thread Stree 0.011 Minding Operating Current: 20.0 m	
Impedance Rating In Ohms: 200.0 single component single primary Frequency Rating: 60.0 hertz single component Maximum Transformer Power Rating: 120.0 watts single component Primary To Secondary Turn Ratio: 1 to 5 10 9 single component Winding Shielding Method: Core grounded single component Body Length: 4.500 inches Body Width: 4.000 inches Body Height: 5.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Vinding Function And Quantity: 1 primary single component and 2 secondary single component Threaded stud single group Minding Operating Current: 2 single group Winding Operating Current: 2 so.0 milliamperes dc single component single primary Thread Streis Designator: Unc single group Thread Streis Designator: 2 single group Thread Streis Designator: 2 single group Thread Streis Designator: Unc single group </td <td>-</td>	-
200.0 single component single primary Frequency Rating: 60.0 hertz single component Maximum Transformer Power Rating: 120.0 watts single component Primary To Secondary Turn Ratio: 1 to 5 to 9 single component Winding Shielding Method: Core grounded single component Body Length: 4.500 inches Body Height: 5.500 inches Body Height: 5.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Minding Function And Quantity: 1 primary single component and 2 secondary single component 1 Thready Qty Per Inch (tpi): 32 single group Winding Operating Current: 26.0.0 millamperes dc single component single primary 27. Ince Streis Designator: Unc single group Fremal Type And Quantity: 7 tab, solder lug	
Frequency Rating: 60.0 hertz single component Maximum Transformer Power Rating: 120.0 watts single component Primary To Secondary Turn Ratio: 1 to 5 to 9 single component Winding Shielding Method: Core grounded single component Body Length: 4.500 inches Body Width: 4.000 inches Body Height: 5.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Minding Function And Quantity: 1 primary single component and 2 secondary single component Threadd stud single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Thread Size: 0.375 inches single group Winding Operating Current: 260.0 milliamperes dc single component single primary Thread Size: 0.375 inches single group Winding Operating Current: 260.0 milliamperes dc single component single primary Thread Size 0.40.0 milliamperes dc single component single primary	
60.0 hertz single component Maximum Transformer Power Rating: 120.0 watts single component Primary To Secondary Turn Ratio: 1 to 5 to 9 single component Vinding Shielding Method: Core grounded single component Body Length: 4.500 inches Body Width: 4.000 inches Body Height: 5.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Minding Function And Quantity: 1 primary single component and 2 secondary single component Thread Stue 1 primary single component and 2 secondary single component Primary single group Vinding Operating Current: 26.0.0 milliamperes dc. single component single primary Chread Stue Stue Stue Stue Stue Stue Stue Stue	
Maximum Transformer Power Rating: 120.0 watts single component Primary To Secondary Turn Ratio: 1 to 5 t0 9 single component Winding Shielding Method: Core grounded single component Body Length: 4.500 inches Body Vidth: 4.000 inches Body Height: 5.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Minding Method: Threaded stud single group Minding Function And Quantity: 1 primary single component and 2 secondary single component Threaded stud single group Minding Function And Quantity: 1 primary single component and 2 secondary single component Thread Size: 0.375 inches single group Minding Operating Current: 260.0 milliamperes dc single component single primary Thread Size: 0.375 inches single group Minding Operating Current: 260.0 milliamperes dc single component single primary Thread Size: 0.175 inches legignator: Unc single group	
Primary To Secondary Turn Ratio: 1 to 5 t0 9 single component Winding Shielding Method: Core grounded single component Body Length: 4.500 inches Body Width: 4.000 inches Body Height: 5.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Minding Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Threaded stud single group Minding Operating Current: 2 single group Minding Operating Current: 2 solo, omilliamperes dc: single component single primary Thread Steis Designator: Unc single group Thread Steis Designator: 2 single group Thread Steis Designator: 2 fore, single group Thread Steis Designator: 2 fore, single group Thread Steis Designator: 2 fore, solder lug Shift Life:	
Primary To Secondary Turn Ratio: 1 to 5 to 9 single component Winding Shielding Method: Core grounded single component Body Length: 4.500 inches Body Width: 4.000 inches Body Height: 5.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 1 treaded stud single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Threaded stud single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Threaded stud single group Winding Group Winding Operating Current: 20.0 milliamperes dc single component single primary Thread Steise 0.375 inches single group Winding Operating Current: 20.0 milliamperes dc single component single primary Thread Steise Designator: Unc single group Thread Steise Designator: Unc single group Thread Steise Designator:<	-
1 to 5 to 9 single component Winding Shielding Method: Core grounded single component Body Length: 4.500 inches Body Width: 4.000 inches Body Height: 5.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Threaded Size: 0.375 inches single group Winding Operating Current: 26.00 milliamperes dc single component single primary Thread Size: 0.375 inches single group Winding Operating Current: 26.00 milliamperes dc single component single primary Thread Series Designator: Unc single group Thread Series Designator: Unc single group Thread Series Designator: 27.00 milliamperes dc single component single primary Thread Series Designator: Unc single group Thread Series Designator: Y tab	
Winding Shielding Method:Core grounded single componentBody Length:4.500 inchesBody Width:4.000 inchesBody Height:5.500 inchesInclosure Type:Hermetically sealedMounting Facility Quantity:4 single groupMounting Method:Threaded stud single groupWinding Function And Quantity:1 primary single component and 2 secondary single componentThready Qty Per Inch (tpi):32 single groupMinding Operating Current:20.00 milliamperes dc single component single primaryThread Stries Designator:Unc single groupThread Stries Designator:20.10 milliamperes dc single component single primaryThread Stries Designator:Unc single groupThread Stries Designator:Unc single groupThread Itype And Quantity:7 tab, solder lugShiff Life:	
Core grounded single component Body Length: 4.500 inches Body Width: 4.000 inches Body Height: 5.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Thready Qty Per Inch (tpi): 32 single group Minding Operating Current: 20:0 milliamperes dc single component single primary Thread Series Designator: Unc single group Thread Series Designator: 10: solder lug Stories group	
Body Length: 4.500 inches Body Width: 4.000 inches Body Height: 5.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.375 inches single group Winding Operating Current: 260.0 milliamperes dc single component single primary Thread Series Designator: Unc single group Thread Series Designator: Unc single group Thread I type And Quantity: 1 tab, solder lug	
4.500 inches Body Width: 4.000 inches Body Height: 5.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.375 inches single group Winding Operating Current: 260.0 milliamperes dc single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 7 tab, solder lug	
Body Width: 4.000 inches Body Height: 5.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.375 inches single group Winding Operating Current: 260.0 milliamperes dc single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 7 tab, solder lug Shelf Life:	
4.00 inches Body Height: 5.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Vinding Function And Quantity: 1 primary single component and 2 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.375 inches single group Vinding Operating Current: 260.0 milliamperes dc single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 7 tab, solder lug	
Body Height: 5.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.375 inches single group Winding Operating Current: 260.0 milliamperes dc single component single primary Thread Series Designator: Unc single group Tarminal Type And Quantity: 7 tab, solder lug Shelf Life:	-
5.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.375 inches single group Winding Operating Current: 260.0 milliamperes dc single component single primary 260.0 milliamperes dc single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 7 tab, solder lug Shelf Life:	
Inclosure Type:Hermetically sealedHounting Facility Quantity:4 single groupMounting Method:Threaded stud single groupWinding Function And Quantity:1 primary single component and 2 secondary single componentThready Qty Per Inch (tpi):32 single groupThread Size:0.375 inches single groupWinding Operating Current:260.0 milliamperes dc single component single primaryThread Series Designator:Unc single groupTerminal Type And Quantity:7 tab, solder lugShelf Life:	
Hermetically sealedMounting Facility Quantity:4 single groupMounting Method:Threaded stud single groupWinding Function And Quantity:1 primary single component and 2 secondary single componentThready Qty Per Inch (tpi):32 single groupThread Size:0.375 inches single groupWinding Operating Current:260.0 milliamperes dc single component single primaryThread Series Designator:Unc single groupTarminal Type And Quantity:7 tab, solder lugShelf Life:	
Mounting Facility Quantity:4 single groupMounting Method:Threaded stud single groupWinding Function And Quantity:1 primary single component and 2 secondary single componentThready Qty Per Inch (tpi):32 single groupThread Size:0.375 inches single groupWinding Operating Current:260.0 milliamperes dc single component single primaryThread Series Designator:Unc single groupTerminal Type And Quantity:7 tab, solder lugShelf Life:	
4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.375 inches single group Winding Operating Current: 260.0 milliamperes dc single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 7 tab, solder lug Shelf Life:	
Mounting Method:Threaded stud single groupWinding Function And Quantity:1 primary single component and 2 secondary single componentThready Qty Per Inch (tpi):32 single groupThread Size:0.375 inches single groupWinding Operating Current:260.0 milliamperes dc single component single primaryThread Series Designator:Unc single groupTerminal Type And Quantity:7 tab, solder lugShelf Life:	
Threaded stud single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.375 inches single group Winding Operating Current: 260.0 milliamperes dc single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 7 tab, solder lug Shelf Life:	
Winding Function And Quantity: primary single component and 2 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.375 inches single group Winding Operating Current: 260.0 milliamperes dc single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 7 tab, solder lug Shelf Life:	-
1 primary single component and 2 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.375 inches single group Winding Operating Current: 260.0 milliamperes dc single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 7 tab, solder lug Shelf Life:	
Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.375 inches single group Winding Operating Current: 260.0 milliamperes dc single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 7 tab, solder lug Shelf Life:	
32 single group Thread Size: 0.375 inches single group Winding Operating Current: 260.0 milliamperes dc single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 7 tab, solder lug Shelf Life:	
Thread Size: 0.375 inches single group Winding Operating Current: 260.0 milliamperes dc single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 7 tab, solder lug Shelf Life:	
0.375 inches single group Winding Operating Current: 260.0 milliamperes dc single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 7 tab, solder lug Shelf Life:	
Winding Operating Current: 260.0 milliamperes dc single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 7 tab, solder lug Shelf Life:	
260.0 milliamperes dc single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 7 tab, solder lug Shelf Life:	
Thread Series Designator: Unc single group Terminal Type And Quantity: 7 tab, solder lug Shelf Life:	
Unc single group Terminal Type And Quantity: 7 tab, solder lug Shelf Life:	
Terminal Type And Quantity: 7 tab, solder lug Shelf Life:	-
7 tab, solder lug Shelf Life:	
Shelf Life:	
	-
N/a	
	N/a

Audio Frequency Transformer - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0