## NSN 5950-00-543-9676

Saturable Reactor - Page 1 of 2

**Reliability Indicator:** 

Not established



View Online at https://aerobasegroup.com/nsn/5950-00-543-9676

Center To Center Distance Between Mounting Facilities Parallel To Length:
2.219 inches and 2.281 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:

1.969 inches and 2.031 inches single mounting facility single center group
Frequency Rating:
400.0 hertz single component
Body Length:
5.000 inches
Body Width:
3.250 inches
Body Height:
4.250 inches
Maximum Operating Temp:
170.0 degrees celsius
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
2 control and 2 primary single component
Saturation Current Rating:
50.0 milliamperes
Thread Size:
0.190 inches single group
Dc Resistance Rating In Ohms:
30.000 single component all control
Winding Power Rating:
1.5 volts-amperes single component all control
Winding Operating Voltage:
30.00 ac volts single component all control
Thread Series Designator:
Unf single group
Terminal Type And Quantity:
8 solder stud
Shelf Life:
N/a
Unit Of Measure:

## NSN 5950-00-543-9676

Saturable Reactor - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0