

View Online at <https://aerobasegroup.com/nsn/5950-00-545-7700>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

3.750 inches

Body Width:

3.375 inches

Body Height:

3.938 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

120.0 milliamperes dc single component single secondary

Winding Operating Voltage:

95.00 ac volts single component single primary and 2.00 ac volts single component single secondary and 4.00 ac volts single component single secondary and 105.00 ac volts single component single primary and 115.00 ac volts single component single primary and 6.00 ac volts single component single secondary and 190.00 ac volts single component single primary and 8.00 ac volts single component single secondary and 90.00 ac volts single component single secondary and 210.00 ac volts single component single primary and 100.00 ac volts single component single secondary and 230.00 ac volts single component single primary and 110.00 ac volts single component single secondary 250.00 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

17 turret

Shelf Life:

N/a

Unit Of Measure:

Fig:

A058b0