

View Online at <https://aerobasegroup.com/nsn/5950-00-548-0491>

Reliability Indicator:

Not established

Overall Length:

12.656 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

8.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

8.000 inches single mounting facility single center group

Overall Height:

10.219 inches

Overall Width:

10.594 inches

Mounting Hole Diameter:

0.438 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Maximum Transformer Power Rating:

5.0 kilovolt-ampere single component

Winding Shielding Method:

External inclosure single component

Distance Between Mounting Facility Centers:

8.000 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Cooling Type:

Fins

Cooling Method:

Self-cooled

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

41.7 amperes ac single component single secondary

Winding Power Rating:

5.0 kilovolt-amperes single component single primary

Winding Operating Voltage:

450.00 ac pounds per hour wet single component single primary

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0

Mil-std (military Standard):

Mil-t-15108c spec.