# NSN 5950-00-548-0491



Power Transformer - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5950-00-548-0491
Reliability Indicator:
Not established
Overall Length:
12.656 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
8.000 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
8.000 inches single mounting facility single center group
Overall Height:
10.219 inches
Overall Width:
10.594 inches
Mounting Hole Diameter:
0.438 inches single group
Frequency Rating:
60.0 hertz single component
Input-output Phase Relationship:
Three phase to three phase single component
Maximum Transformer Power Rating:
5.0 kilovolt-ampere single component
Winding Shielding Method:
External inclosure single component
Distance Between Mounting Facility Centers:
8.000 inches single mounting facility single center group
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:

4 single group

#### **Mounting Method:**

Unthreaded hole single group

# **Cooling Type:**

Fins

# **Cooling Method:**

Self-cooled

# **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

# **Winding Operating Current:**

41.7 amperes ac single component single secondary

# **Winding Power Rating:**

5.0 k1lovolt-amperes single component single primary

# **Winding Operating Voltage:**

450.00 ac pounds per hour wet single component single primary

# NSN 5950-00-548-0491

Power Transformer - Page 2 of 2



Terminal Type And Quantity:
4 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A058b0

Mil-std (military Standard):

Mil-t-15108c spec.