

View Online at <https://aerobasegroup.com/nsn/5950-00-549-1969>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.031 inches single mounting facility single center group5.031 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.571 inches single mounting facility single center group4.571 inches single mounting facility single center group

Mounting Hole Diameter:

0.202 inches single group and 0.202 inches single group and 0.208 inches single group0.208 inches single group

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

6.000 inches 6.000 inches

Body Width:

3.938 inches 3.938 inches

Body Height:

3.375 inches 3.375 inches

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Unthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

2 primary single component and 2 primary single component and 5 secondary single component5 secondary single component

Winding Operating Current:

660.0 milliamperes ac single component 2nd secondary

Winding Power Rating:

2.0 volts-amperes single component 3rd secondary17.16 volts-amperes single component 2nd secondary

Winding Operating Voltage:

99.60 ac volts single component 2nd primary115.00 ac volts single component 1st secondary

Special Features:

2 primary windings; 5 secondary windings

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0